

FIG. 1




FIG. 2

Subscriber data table

Subscriber# 1	Subscriber registration information
	Subscriber identification number
	Subscriber type
	Maximum allowable Sch rate
	Maximum allowable hand-off rate
Subscriber# 2	Subscriber registration information
	Subscriber identification number
	Subscriber type
	Maximum allowable Sch rate
	Maximum allowable hand-off rate
• • •	• • •
Subscriber# n	Subscriber registration information
	Subscriber identification number
	Subscriber type
	Maximum allowable Sch rate
	Maximum allowable hand-off rate


FIG. 3

Call number	Hand-off BTS information	Forward side rate information[kbps]	Reverse side rate information[kbps]
1	0	9.6	9.6
2	1	19.2	9.6
⋮	⋮	⋮	⋮
~	~	~	~
N	2	153.6	153.6

(Values in the table are exemplary)


09939459-082401

FIG. 4




Sch Setting (Forward)

FIG. 5




Sch Setting (Reverse)

FIG. 6




Sch Setting (Forward) When (Exceeding) Maximum Rate

FIG. 7



Sch Setting (Reverse) When Maximum Rate

FIG. 8



0939459-082401

FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

Recommended rate database

Recommended rate	Rank R	Timer	
9. 6kbps	1	T1	Subscriber#1 Subscriber#6
	2	T2	
	3	T3	Subscriber#3 Subscriber#10 Subscriber#38
	4	T4	
	5	T5	
	6	T6	
9. 6 × 2kbps	7	T7	
	8	T8	
	9	T9	
	10	T10	
	11	T11	
	12	T12	
.	.	.	
.	.	.	
.	.	.	

FIG. 15




FIG. 16

